

Seacork



THE Austrol Technology Group is proud to announce that it has secured the Australasian Distribution rights for Seacork of France. Seacork is one of the lightest and most comfortable decking surfaces underfoot. It can be applied to both external and internal applications. Seacork can be left in its natural state or can be sealed or stain/sealed with our range of teak/cork sealers. Installation is very easy with only very basic tools required (tape measure, cutting blade, trowel and caulking gun). Seacork comes in grooved sheets ready for caulking with black or white caulking compound. Seacork is available in 47mm strip, sheets with grooves and plain sheet for detail edging or for making logos. To assist installation a download is available off our website (installation on a catamaran).

Benefits of Seacork include:

- Light weight, durable surface;
- Cost effective;
- Easy installation;
- Renewable – natural resource;
- Easy to maintain and repair;
- Great heat insulation properties;
- Excellent sound insulation properties;
- Limited slip when wet.

Technical

Density: 400 kg/m³

Compressibility: 15/20%

Traction: min. 15 d.N/cm²

Thickness: 8mm, grooves 4 X 4mm -

Weight: 3.2 kg/m² (External Use)

Thickness: 4 mm, grooves 4 X 2mm -

Weight: 1.6 kg/m² (Internal Use)

Heat Insulation (at 20° C)

Specific Heat >1500 J/kg.K

Thermal Diffusivity < 1.60.10⁻⁷ m².S

Thermal Conductibility 0.05/0.06 W/mK

Seacork will be sold by:

Seacork Australasia

78 Kalaroo Road

Redhead NSW 2290, Australia

P: 02 4935 2260

F: 02 4935 2225

E: (temporary) seacorkoznz@hotmail.com

E: (future) enquiry@seacork.com.au

W: www.seacork.com.au

It will also be available at most chandlers, marinas/installers.