

+APPLICATIONS :

SEACORK®DECK is used as a non-slip liner for boat decks. Thanks to its aesthetics and insulating properties, this natural material offers the best qualities required for a super comfortable, marine resistant, secure and longlasting decking option. SEACORK®DECK is available in plates (sheets) and blades (strips).

+COMPOSITION :

SHEET :

- Cork Granulate (2 to 4 mm)
- Binder : thermoplastic resin

+SIZES :

Dimensions (mm)	Tolerance	Thickness (mm)	Tolerance
1000X500	±8mm	3, 4, 5 & 6	±0,5 mm
2000x500		3, 4, 5,6, 8 & 12	
2000x 47 (73, 103 & 125)		6, 8, 12	

+AVANTAGES :

- ✓ Very good heat insulator
- ✓ Very good sound insulator
- ✓ Does not rot
- ✓ Naturally anti-slip, even underwater
- ✓ Excellent dimensional stability
- ✓ Light weight
- ✓ Easy maintenance
- ✓ Easy application
- ✓ Easy repair

+PERFORMANCE :

MECHANICAL :

Density	400 kg/m ³	ISO 7322
Traction	Mini 15 daN/cm ²	ISO 7322
Compressibility	15 à 20%	ISO 7322
Lenghtening	Mini 10%	ISO 7322
Weight for thick. 8 mm	≈3,2 kg/m ²	ISO 7322
Weight for thick. 4 mm	≈1,6 kg/m ²	ISO 7322

THERMAL :

Specific heat :	> 1500 J/kg.K	
Thermal Conductibility	(λ) 0,05 à 0,06 W/m.K	
Thermal diffusivity	< 1,60.10 ⁻⁷ m ² .s	

+CONSERVATION ET STOCKAGE :

12 month in good storage condition at 20°C (+-3°C) and 60% humidity (+- 5%)

+WARRANTY : 5 years